

Fascetta Bifilare a Vite W1

Double Wire Screw Clamp W1

| Cod. | Ø min. mm | Ø max mm | M | S1 mm |
|--------|--------------|-------------|---|----------|
| BV0095 | 9,5 | 12 | 3 | 1,5 |
| BV0115 | 11,5 | 14 | 3 | 1,5 |
| BV0125 | 12,5 | 15 | 3 | 1,5 |
| BV0130 | 13 | 16 | 3 | 1,8 |
| BV0155 | 15,5 | 19 | 3 | 1,8 |
| BV0170 | 17 | 20 | 3 | 1,8 |
| BV0185 | 18 | 22 | 4 | 2 |
| BV0190 | 19,5 | 23 | 4 | 2 |
| BV0215 | 21,5 | 25 | 4 | 2 |
| BV0235 | 23,5 | 27 | 4 | 2,2 |
| BV0250 | 25 | 29 | 4 | 2,2 |
| BV0270 | 27 | 31 | 4 | 2,2 |
| BV0305 | 30,5 | 35 | 4 | 2,2 |
| BV0355 | 35,5 | 40 | 4 | 2,2 |
| BV0435 | 43,5 | 49 | 5 | 2,5 |
| BV0980 | 98 | 105 | 8 | 2,8 |
| BV1450 | 145 | 160 | 6 | 2,4 |

Caratteristiche

Materiale: Acciaio zincato W1

Utilizzo:

Fascette consigliate per serrare tubi con spirali in rilievo; garantiscono un serraggio ottimale anche in presenza di tubi molto morbidi e con spessori sottili.

Product specification

Material: Zinc plated steel W1

Use:

Hose clamp recommended for hoses with spiral reinforcement in relief. They guarantee an optimal tightening even with very soft hoses or those with a thin thickness.

