

FR - GR

Fascetta con Carrello Riapribile W2

Fast Release Hose Clamp W2

INOX
Stainless Steel

Cod.	Ø min. mm	Ø max mm	B1 mm	B2 mm	Coppia di Serraggio Safe Working Torque	U.V.
FR080	60	80	9	16,4	3 Nm	50
FR090	60	90	9	16,4	3 Nm	50
FR110	60	110	9	16,4	3 Nm	50
FR135	60	135	9	16,4	3 Nm	50
FR150	60	150	9	16,4	3 Nm	50
FR180	60	180	9	16,4	3 Nm	50
FR215	60	215	9	16,4	3 Nm	50
FR275	60	275	9	16,4	3 Nm	50
FR325	60	325	9	16,4	3 Nm	50
GR080	60	80	12	19,4	5 Nm	50
GR090	60	90	12	19,4	5 Nm	50
GR100	60	100	12	19,4	5 Nm	50
GR110	60	110	12	19,4	5 Nm	50
GR135	60	135	12	19,4	5 Nm	50
GR150	60	150	12	19,4	5 Nm	50
GR175	60	175	12	19,4	5 Nm	50
GR215	60	215	12	19,4	5 Nm	50
GR275	60	275	12	19,4	5 Nm	50
GR325	60	325	12	19,4	5 Nm	50

Caratteristiche

Materiale Banda e Carter:

Acciaio inox AISI 430

Materiale Vite: Acciaio al carbonio

Caratteristiche Banda: Nastro dentato

Caratteristiche Vite: Con taglio combinato

Product specification

Band and Housing Material:

Zinc plated steel AISI 430

Screw Material: Carbon steel

Band Features: Threaded Band

Screw Features:

Hexagonal head with slot and cross

