

NB - NN

Fascetta Nylon

Cable Tie

Cod. Bianco White Code	Cod. Nero Black Code	Lungh. Length mm	Largh. Width mm	Tenuta minima Min. hold kg	U.V.
NB100/2	NN100/2	100	2,5	11	100
NB150/2	NN150/2	150	2,5	11	100
NB200/2	NN200/2	200	2,5	11	100
NB140/3	NN140/3	140	3,6	22	100
NB200/3	NN200/3	200	3,6	22	100
NB250/3	NN250/3	250	3,6	22	100
NB280/3	NN280/3	280	3,6	22	100
NB370/3	NN370/3	370	3,6	22	100
NB200/4	NN200/4	200	4,8	29	100
NB250/4	NN250/4	250	4,8	29	100
NB300/4	NN300/4	300	4,8	29	100
NB370/4	NN370/4	370	4,8	29	100
NB430/4	NN430/4	430	4,8	29	100
NB300/7	NN300/7	300	7,6	72	100
NB370/7	NN370/7	370	7,6	72	100
NB450/7	NN450/7	450	7,6	72	100
NB550/7	NN550/7	550	7,6	72	100
NB750/7	NN750/7	750	7,6	72	100
NB760/9	NN760/9	760	9	104	100
NB900/9	NN900/9	900	9	104	100



Caratteristiche

Materiale:

Nylon 6/6 classe autoestinguenza
UL 94V-2

Utilizzo:

Cablaggio di fili e cavi elettrici,
ed in molteplici altri campi
(agricolo, industriale, hobbystico ecc.)

Temperatura di Utilizzo: -30° +70° C.

Caratteristiche Specifiche:

Testa e dente ad alta resistenza
alla trazione - estremità ricurva
per inserimento facilitato.

Product specification

Material:

Nylon 6/6 auto extinguishing class
UL 94V-2

Use:

Ideal for clamping single or bundled
cables. Also suitable for use in many other
fields such as agriculture, hobby, do-it-
yourself, etc.

Temperature of Use: -30° +70° C.

Specific Features:

High tensile strength buckle head and
tooth, curved end for easy insertion.