

THO

Piede Antivibrante Zincato con Stelo Girevole

Antivibration Zinc-plated Mount with Revolving Spindle

| Cod. | A | M | B | H | Carico max Statico Max Load daN | U.V. |
|-----------|-----|------|-----|----|------------------------------------|------|
| A4THO400 | 40 | 10MA | 50 | 34 | 600 | 4 |
| A4THO600 | 80 | 12MA | 100 | 44 | 800 | 4 |
| A4THO1200 | 120 | 16MA | 100 | 48 | 1000 | 4 |
| A4THO3000 | 160 | 20MA | 150 | 63 | 2000 | 4 |
| A4THO4000 | 200 | 20MA | 150 | 63 | 3000 | 4 |

Caratteristiche

Materiale base: Acciaio zincato

Tipo base: Antivibrante

Corredo base: Suola in NBR 70 shore

Materiale stelo: Acciaio zincato

Tipo stelo: Girevole

Corredo stelo: Dado

Presentazione prodotto:

Stelo fornito già assemblato alla base

Product specification

Base material: Zinc plated steel

Base type: Antivibration

Base outfit: NBR 70 shore plate

Spindle material: Zinc plated steel

Spindle type: Revolving

Spindle outfit: Nut

Product presentation:

Spindle supplied already assembled to the base

