

# XS95

## Piede Snodato con Base e Stelo in Acciaio Inox AISI 304

### Articulated Foot with AISI 304 Stainless Steel Base and Stud

**INOX**  
Stainless Steel

Cod.	A	M	B	C	H	Chiave Spanner	Carico Max Max Load daN	U.V.
A5XS95/16060	95	16MA	60	103	26	13	2200	8
A5XS95/16090	95	16MA	90	133	26	13	2200	8
A5XS95/16105	95	16MA	105	148	26	13	2200	8
A5XS95/16125	95	16MA	125	168	26	13	2200	8
A5XS95/16155	95	16MA	155	198	26	13	2200	8
A5XS95/16165	95	16MA	165	208	26	13	2200	8
A5XS95/16205	95	16MA	205	248	26	13	2200	8
A5XS95/20086	95	20MA	86	132	26	17	2400	8
A5XS95/20116	95	20MA	116	162	26	17	2400	8
A5XS95/20141	95	20MA	141	187	26	17	2400	8
A5XS95/20206	95	20MA	198	244	26	17	2400	8
A5XS95/24096	95	24MA	96	142	26	19	2600	8
A5XS95/24122	95	24MA	122	168	26	19	2600	8
A5XS95/24152	95	24MA	152	198	26	19	2600	8
A5XS95/24182	95	24MA	182	228	26	19	2600	8
A5XS95/24300	95	24MA	300	346	26	19	2600	8

#### Caratteristiche

##### Materiale Base:

Anima interna in poliammide + FV;  
rivestimento esterno in acciaio inox AISI 304; antivibrante in gomma termoplastica SEBS 55 shore colore nero.

##### Materiale Stelo: Acciaio inox AISI 304

##### Tipo Stelo: Snodato

##### Presentazione Prodotto:

Stelo fornito assemblato alla base

##### Note:

L'antivibrante costampato consente una perfetta aderenza con la base in acciaio. La conseguente assenza di cavità interne rende il piede estremamente sanificabile.

#### Product specification

##### Base Material:

Internal part made of reinforced polyamide;  
external covering made of stainless steel AISI 304; anti-slip pad made of SEBS Rubber 55 shore black colour.

##### Spindle Material: Stainless steel AISI 304

##### Spindle Type: Articulated

##### Product Presentation:

Spindle supplied assembled to the base

##### Note:

The comoulded anti-slip rubber pad adheres perfectly to the steel base thus the absence of internal cavities makes the foot extremely easy to clean and sanitize.



Ø95

