

T03SP/ACC

Tubo Spirale Acciaio Alimentare Aspirazione e Mandata

Food Quality Spiral Steel Suction and Delivery Hose



Ø interno inner mm	Pressione di Eserc. Working Pressure bar	Pressione di Scoppio Burst Pressure bar	Raggio di curvatura Bending Radius mm	Peso Teorico Weight gr/mt	Lungh. Rotolo Roll Length
12	4	20	40	195	60 MT
14	4	20	50	225	60 MT
16	4	20	60	263	60 MT
18	4	20	60	290	60 MT
20	4	20	70	350	60 MT
25	3	15	90	495	60 MT
30	3	15	110	585	60 MT
32	3	15	110	640	60 MT
35	3	15	120	695	60 MT
38	3	15	130	790	30 MT
40	3	15	140	860	30 MT
45	3	15	160	1095	30 MT
50	3	15	180	1225	30 MT
60	2,5	8	210	1685	30 MT
76	2,5	7	270	2185	30 MT
80	2,5	7	280	2335	20 MT

Per aspirazione e passaggio di liquidi.
Estremamente flessibile, resistente allo schiacciamento e dotato di eccellente raggio di curvatura. Conforme alla normativa EU 10/2011 (classi A, B, C).

Hose for suction and delivery of liquids.
Extremely flexible, crush resistant and endowed with an excellent bending radius. In compliance with the EU Regulation 10/2011 (class A, B, C).

Caratteristiche Tecniche

Struttura:

PVC flessibile, liscio internamente ed esternamente; spirale di rinforzo in acciaio armonico zincato

Colore: Trasparente

Temperatura: +60°C - 10°C

Technical Features

Structure:

Flexible PVC hose, internally and externally smooth, with zinc-plated steel spiral reinforcement

Colors: Transparent

Temperature: +60°C - 10°C